

## OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on April 26, 2004.

KRYTON INTERNATIONAL INC.
8280 ROSS STREET
VANCOUVER, BRITISH COLUMBIA V5X 4C6
CANADA
800-267-8280
604-324-8280

Facility: VANCOUVER, BRITISH COLUMBIA, CANADA

## Protective (Barrier) Materials

Trade Designation  Concrete Admixtures [1]	Water Contact Size Restriction	Water Contact Temp	Water Contact Material
Concrete Admixtures			
KIM	>= 200 gal.	C. HOT	CMNT
KIM-HS	>= 200 gal.	C. HOT	CMNT
Krystol Internal Membrane	>= 200 gal.	C. HOT	CMNT
Krystol T1	>= 200 gal.	C. HOT	CMNT
Krystol T2	>= 200 gal.	C. HOT	CMNT
Krystol Waterstop	>= 200 gal.	C. HOT	CMNT

<sup>[1]</sup> Maximum use level of admixture is 2% of cement by mass.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.

## NSF International

RECOGNIZES

## KRYTON INTERNATIONAL INC.

AS COMPLYING WITH ANSI/NSF 61.

PRODUCTS APPEARING IN THE NSF OFFICIAL LISTING ARE AUTHORIZED TO BEAR THE NSF MARK.





Certification Program Accredited by the American National Standards Institute



Certification Program Accredited by the Standards Council of Canada

This certificate is the property of NSF International and must be returned upon request. To verify certification, call 800 NSF-MARK or (1) 734 769-8010.

Smooth M.

Connece

Ronald M. Coiner, General Manager Water Distribution Systems