

Special release agent for moulds made of wood and metal.

Edition: 1 09/2012

Technical department

### Description:

Oily liquid specially formulated for moulds made of wood and metal.

### Uses:

It is used in all types of moulds made of wood or metal both in work and prefab industry. It can be used on concretes placed by traditional methods as vibrated, self-compacting, etc.

### Technical features:

Aspect	Oily liquid
Colour/s	Amber translucent
Density	0,85 kg/lt

### Features & benefits:

\* EASE TO APPLYING\* PROTECTS THE MOULDS\*  
SOLUBLE IN GAS OIL AND OTHER HYDROCARBONS\* HIGH  
PERFORMANCE\*

### Surface preparation:

The surface of the moulds must be cleaned, free of dust, particles, wastes of mortars or concretes and dry.

### Clean up:

The tools used can be cleaned with cleaning solvent

### Coverage:

5 to 10 sqm/lt not diluted, diluted 15 to 30 sqm/l

### Application

- Shake strongly the content of the package before using.
- Apply preferably as the product is provided.
- Soluble in gas oil and other hydrocarbons.
- The application must be done with brush, roller, spray can before placing the metallic armour.
- The concretes which going to be painted on or cladding with mortars must be washed with plenty of water and brushed with brushes to remove wastes of release-agents.

### Packaging:

Available in packs of:

5 Litre 4 Packages per box  
25 Litre

### Storage:

1 year in their original packages, protected from the weather and stored in cool and dry places.

### Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.