

### Description:

Water-soluble primer, designed to ensure good adherence of RELAIS high quality synthetic resins based in water dispersion and special charges.

### Uses:

As a primer to properly ensure the adhesion of our RELAIS plastic coating. It can be applied to both new surfaces and painted surfaces after preparation.

### Features & benefits:

\* IMPROVES ADHESION \* BACKGROUND COLOR FOR REALIS \* VERY GOOD HOLDER ADHESION \* WATERPROOF PROPERTIES \* WEATHERPROOF \*

### Surface preparation:

Must be clean, without greases, oils, dust or loose particles, being compact, dry or slightly moistened.

### Clean up:

With plentiful clean water while the product still fresh.

### Application

- Mix the content of each package thoroughly before using the product.
- Apply using a paint brush or roller.
- Dilute in water up to 50%(maximum) and then apply one single coating.
- Leave to stand for at least 8 hours before applying RELAIS.

### Packaging:

Available in packs of:

- 6 Kilos
- 25 Kilos

### Storage:

2 years, in their original packages and properly closed, stored in a fresh and dry place and protected from the weather.

### Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.

### Technical features:

Colour/s	Colour/s: regarding color chart
Density	1,67 Kg./Lt. +- 0,05
Dry for repainting	8 hours at 20°C
Temperature of work	5 to 30°C
Viscosity	50.000 +- 10.000 mPa.s

### Coverage:

10 sqm per kg and per layer

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña  
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es